

# A7

## Highlighting Tile SPECIFICATION SHEET

- Enhancing safety initiatives such as 5S & 6S programs
- Provides a more durable alternative to tape and paint
- Clear tiles allow for under mat lighting
- Standard lug connection system allows mixing of tile types
- The underside leg structure provides clearance for air lines, cords, and hoses, thereby eliminating trip hazards



<b>DIMENSIONS</b>	18 in x 6 in x 1 in
<b>WEIGHT</b>	2 lbs
<b>COMPOSITION</b>	100% PVC tile
<b>TEAR STRENGTH (ASTM D624)</b>	303 lbs/in
<b>TENSILE STRENGTH (ASTM D412)</b>	Stress: 1630 PSI Strain: 150%
<b>DUROMETER</b>	Shore hardness "A" 85 (+/-5)
<b>FLAMMABILITY</b>	.61 watts/cm <sup>2</sup> = Class 1 fire resistant
<b>TABER ABRASION (SAE J1530)</b>	Negligible wear
<b>FRICTION (ASTM D1894)</b>	Static: 0.90 Dynamic: 0.84
<b>MAX LOADING</b>	1429 PSI
<b>WARRANTY</b>	Lifetime warranty against manufacturer's defects

ANTI-FATIGUE



ANTI-SLIP



CLASS 1  
FIRE RESISTANT

